

CABINET 6U 600X450

ViRack

DATASHEET: LW241106 v1

REFERENCE	DESCRIPTION	COLOR	PCS
MU6U645	Cool rolled steel Tempered smoky-gray glass with thickness of 5mm.	GREY WHITE BLACK	1 PC

MU6U645




Widely used in networking, educational and broadcasting systems, as well as in telecommunications. Suitable for placing server computers and precision electronic equipments.

APPLICATION


- Smoky-gray glass front door.
- Easily mounted on walls, can also be placed on floor after installing the frame or feet.
- **Loading capacity:** 60KG.
- Top and bottom wiring channel could be closed.
- Removable front door and side panels, easy to install and maintain.
- Surface finish: Degreased, acid cleaned, phosphoric, water cleaned, electro-static powder coating, meet ROHS standard.

PRODUCT DIMENSIONS


mm Unit of Measurement:mm




Left




Front




Side




Back




Top



Front(without glass)



A-A Section



Mounting dimension

CABINET 12U 600X450

ViRack

ACCESSORIES

S/N	SPECIFICATION	PCS	UDS	MATERIAL	SURFACE FINISH	REMARK
1	Frame	4	PCS	1.2mm cold rolled steel	Powder coated	
2	Front door	1	PCS	1.2mm cold rolled steel	Powder coated	B type door
3	Side door	2	PCS	1.2mm cold rolled steel	Powder coated	With lock
4	Back door	1	PCS		Powder coated	
5	Lock	1	PCS	1.5mm cold rolled steel		
6	Mounting rail	4	PCS	1.2mm cold rolled steel	Powder coated	
7	Mounting plate	1	PCS	1.2mm cold rolled steel	Powder coated	
8	Cable inlet cap	2	PCS		Powder coated	
9	Screws & Nuts	10	Packs			
10	Wrench	1	PCS			

CONSTRUCTION

PART No.	U	WIDTH	DEPTH	HEIGHT	PACKAGING (MM)
MUR6U645	6	600MM	450MM	-	615 x 515 x 180
MUR9U645	9	600MM	450MM	-	615 x 515 x 180
MUR12U645	12	600MM	450MM	-	1310 x 1090 x 250
MUR15U645	15	600MM	450MM	-	1440 x 1090 x 250
MUR18U645	18	600MM	450MM	-	1600 x 1090 x 250

